

Jig Grinder

1280 Series

The Moore Tool Company, a leader in precision machine tool design and manufacture, produces a complete line of jig grinding machines and accessories.

The 1280 Series Jig Grinder is available in three models (CPZ, CPZ-E and CPWZ) to address your specific precision grinding requirements. These CNC-controlled jig grinding machines have multiple, programmable axes (four simultaneously controlled) for complex two- and three-dimensional features.

Features

- Large travels for large work or multiple part setups
- Fanuc multi-axis control and PC front-end with customized touchscreen user interface
- Moore ProGrind[®] for improved tool and labor cost savings

Moore ProGrind[®] Options

- State-of-the-art sensor technology (Moore AutoSize[®] and Moore AutoGrind)
- Automatic tool changer (up to 20 tools)
- Automatic tool changer electric spindle: 3,000 to 60,000 rpm
- Air spindles: 9,000 to 175,000 rpm (five spindles)
- Electric spindles: 15,000 to 80,000 rpm (three spindles)
- Flood coolant system with chiller
- Machine enclosure
- Single-axis or two-axis rotary tables
- Fire suppression system
- Vapor extraction system
- On-machine inspection/probing



Specifications



Moore ProGrind® Electric Grinding Spindle

With today's electric grinding spindle technology, constant torque is maintained throughout the speed range of 3,000 to 60,000 rpm. High accuracy radial run-out and superior repeatability tool to tool, helps ensure accuracy when using the 20 tool ATC. The spindle accepts a full-range of HSK-E 25 tool holders.

Capacity	
Table working surface	812 mm x 1320 mm (32.0 x 52.0 in.)
Inside distance between risers	965 mm (38.0 in.)
Tabletop to bottom of bridge	520 mm (20.5 in.)
Travel (X axis)	1320 mm (52.0 in.)
Travel (Y axis)	820 mm (32.3 in.)
U-axis travel (programmable)	3,6 mm (0.140 in.)
U-axis travel (main coarse adjustment)	11 mm (0.43 in.) behind centerline of main spindle to 28,5 mm (1.125 in.) beyond center
Table top to U-axis mounting flange	431,8 mm to 924 mm (17.0 in. to 36.39 in.)
Table top to bottom of ATC electric grinding spindle	264 mm to 757 mm (10.4 in. to 29.8 in.)
W-axis spindle housing vertical travel	350 mm (13.8 in.)
Z-axis vertical slide travel	140 mm (5.5 in.)
Taper adjustment range	0 to 1.5° from centerline (3° included angle over full vertical travel.)
Grinding hole diameter range	0,4 to 127 mm (0.016 to 5.0 in.); or to 343 mm (13.5 in.) with optional extension plates
Load carrying capacity	1360 kg (3000 lbs)

Speeds and Feeds

Traverse speed: X, Y, W, Z axis	0,0001 – 2000 mm/min. (0.00001 – 80.0 in./min.)
Spindle speeds (planetary mode)	1 to 300 rpm
Air turbine and electric grinding spindle speeds	6,000 to 175,000 rpm
Reciprocation stroke rate (25,4 mm / 1 in.)	0 – 190 cycles/min.

Accuracy

Positioning: Step Gauge

Deviation in full travel: X axis	2,5 µm (100.0 µin.)
Deviation in full travel: Y axis	2,0 µm (80.0 µin.)

Positioning Accuracy: VDI/DGQ 3441

Positional uncertainty P: X axis	2,5 µm (100.0 µin.)
Positional uncertainty P: Y axis	2,0 µm (80.0 µin.)
Positional uncertainty P: W axis ¹	2,0 µm (80.0 µin.)
Positional uncertainty P: Z axis ²	4,0 µm (160.0 µin.)
Positional deviation Pa: X axis	1,5 µm (60.0 µin.)
Positional deviation Pa: Y axis	1,5 µm (60.0 µin.)
Positional deviation Pa: W axis ¹	1,5 µm (60.0 µin.)
Positional deviation Pa: Z axis ²	3,0 µm (120.0 µin.)

Contouring Accuracy

X, Y & C at 250 mm/min., measuring a 200 mm (8 in.) ring gauge	3,0 µm (120.0 µin.)
--	---------------------

Geometric: Squareness (Full Travel)

Spindle housing travel: X-Y plane	3,0 µm (120.0 µin.)
-----------------------------------	---------------------

Geometric: Alignment

Parallelism of spindle centerline to column guideways	3,0 µm (120.0 µin.)
---	---------------------

(All statements concerning accuracy are based on calibration temperature of 20 +/- 0.5 degrees C [68 +/- 1.0 degrees F])

¹Not applicable to CPZ and CPZ-E Models

²Not applicable to CPZ Model



Moore Tool Company, Inc.

800 Union Avenue
Bridgeport, CT 06607-0088
USA

Phone: 203 366 3224
Fax: 203 367 0418
Email: sales@mooretool.com
www.mooretool.com

Moore Special Tool AG

In der Leberzen 25
8902 Urdorf
Switzerland

Phone: +41 (0)78 881 95 16
Email: europeansales@mooretool.com
www.mooretool.com

Moore Nanotechnology Systems, LLC

230 Old Homestead Highway
Swanzy, NH 03446
USA

Phone: 603 352 3030
Fax: 603 352 3363
Email: sales@nanotechsys.com
www.nanotechsys.com